



Living in an
environment
of comfort



Automatic air flow
in four directions



- HAV series
- Operating modes: cooling/heating/dehumidification/ventilation
 - Stable operation from -25 °C to +48 °C
 - Wi-Fi control Option
 - Remote control with real-time mode and backlight
 - Anti-corrosion "Blue Fin" coating
 - Multi-stage filter
 - Autonomous control and maintenance of plus temperature in the house (+8 °C)
 - Pre-heating of the tray of the outdoor unit
 - Turbo mode
 - Autorestart
 - Hot start

I-Feel function

Stable operation at -25

7 speeds of the fan

Self-diagnosis complex

AUTO CLEAN

Automatic defrosting

Record-breaking efficient SEER cooling (A++)

Record-breaking efficient SCOP heating (A+++)

Record low noise level of 26 dB (A)

	SUPER DC INVERTER			
	EACS/I-09HAV/ N8_22Y	EACS/I-12HAV/ N8_22Y	EACS/I-18HAV/ N8_22Y	EACS/I-24HAV/ N8_22Y
Specifications				
Cooling Capacity, Btu/h	9212(3800-12966)	11976(3070-15012)	18084(2900-21496)	24200(6800-30200)
Heating Capacity, Btu/h	10236(3071-14501)	13000(3071-16036)	19107(3583-23884)	26000(6150-32200)
Cooling Capacity, W	695 (100 - 1300)	962 (220 - 1400)	1501 (100 - 2300)	2030 (450 - 2900)
Heating Capacity, W	700 (150 - 1400)	953 (220 - 1550)	1393 (240 - 2350)	2000 (350 - 3000)
Rated Voltage V/Hz	220-240V-50Hz	220-240V-50Hz	220-240V-50Hz	220-240V-50Hz
SEER/SCOP	A++/A+++	A++/A+++	A++/A+++	A++/A+++
Air Flow Volume, m3/h	610	680	1000	1250
Sound Pressure Level, dB (A)	25	24	26	33
Appliance dimensions. Indoor unit (W*D*H), mm	825×293×196	825×293×196	982×311×221	1075×333×246
Appliance dimensions. Outdoor unit (W*D*H), mm	732×555×330	732×555×330	802×555×350	958×660×402
Package dimensions. Indoor unit (L*W*H), mm	870×349×257	870×349×257	1039×377×287	1128×406×323
Package dimensions. Outdoor unit (L*W*H), mm	791×373×590	791×373×590	869×395×594	1029×453×715
Net/Gross weight. Indoor unit, kg	9,5/11,5	9,5/11,5	12,5/15	16/19
Net/Gross weight. Outdoor unit, kg	23,5/26	24,5/27	30,5/33,5	41,5/46
Outer Diameter of Pipe (Liquid / Gas Pipe), inch	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	1/4" / 5/8"
Connection pipe - max distance (Length/Height)	15 / 10	15 / 10	25 / 10	25 / 10
Operation ambient temperature range (Cooling / Heating), °C	-15 - +50 / -25 - +30	-15 - +50 / -25 - +30	-15 - +50 / -25 - +30	-15 - +50 / -25 - +30



Effective work all year round

The HAV split system works effectively not only for cooling, but also for heating at -25 °C outside, while consuming less electricity than household heating systems.